









Apply to T slot groove form


316 Stainless steel housing. Cutting fluid resistant, Corrosion resistant



SPECIFICATION

TYPE / CHARACTERISTIC	AL-30MDF	AL-30MN	AL-30MP
SWITCHING LOGIC	Normally Open	Solid State Output, Normally Open	
SENSOR TYPE	2 Wire Solid State	NPN Current Sinking	PNP Current Sinking
OPERATING VOLTAGE	8~30V DC	5~30V DC	
SWITCHING CURRENT	1 ~ 50 mA	0 ~ 200 mA	
SWITCHING RATING	1.5 W Max.	6 W Max.	
Current Consumption	NONE	AC 17000A	AC 17000A
VOLTAGE DROP	4.0V Max. @ 50mA DC	0.8 V Max. @ 200 mA DC	
LEAKAGE CURRENT	200 μA Max.	0.01 mA Max.	
INDICATOR	Red LED	Red LED	Green LED
CABLE	Φ3,6, 2C, Grey Oil-Resistant PU	Φ3.6, 3C, Grey Oil-Resistant PU	
SENSITIVITY	60 Gauss	60 Gauss	
SWITCHING FREQUENCY	25 Hz	25 Hz	
TEMPERATURE RANGE	-20~80℃	-20~80℃	
SHOCK	50 G	50 G	
VIBRATION	9 G	9 G	
ENCLOSURE CLASSIFICATION	IP 68 (GB/T 4208-2017)	IP 68 (GB/T 4208-2017)	
PROTECTION CIRCUIT	Power reverse protection Surge suppression overload protection short circuit protection		
CE Certificate NO.	**E8A 053334 0014**	**E8A 053334 0014**	**E8A 053334 0014**
3C Certificate NO.	/	/	/
CNEx Certificate NO.	**CNEx21.2238X**	**CNEx21.2239X**	
Connection Diagram			

AL-30MDF
AL-30MDF-QJ8
AL-30MDF-QC12(QJ12)
AL-30MDF-EZ2M




AL-30MN(P)
AL-30MN(P)-QJ8
AL-30MN(P)-QC12(QJ12)
AL-30MN(P)-EZ3M


Options: See part number codes descriptions on page 09

QUICK CONNECTOR (IEC61076-2-101/IEC61076-2-104)

2 wire connector wiring



3 wire connector wiring



IP68 REACH CE CNEx RoHS